



- Energy-efficient compressor
- Refrigeration-grade premium $\Phi 7\text{mm}$ copper tubing and aluminum fin condenser coil
- Cooling range from 54~126°F, Heating range from 14~90°F

Model			DHP5018E1000A	DHP5024E1000A	DHP5030E1000A	DHP5036E1000A	DHP5042E1000A	DHP5048E1000A	DHP5060E1000A
Power Supply			208-230V/1N/60Hz	208-230V/1N/60Hz	208-230V/1N/60Hz	208-230V/1N/60Hz	208-230V/1N/60Hz	208-230V/1N/60Hz	208-230V/1N/60Hz
Cooling	Capacity	Btu/h	16500	22000	27400	33000	38000	44000	55000
	SEER2 / EER2	Btu/h.w	14.3 / 11.7	14.3 / 11.7	14.3 / 11.7	14.3 / 11.7	14.3 / 11.7	14.3/11.2	14.3/11.2
Heating	Capacity	Btu/h	16500	22000	27500	33000	38000	45000	55000
	HSPF2	Btu/h.w	7.50	7.50	7.50	7.50	7.50	7.50	7.50
Compressor Type / Brand			Scroll	Scroll	Scroll	Scroll	Scroll	Scroll	Scroll
Fan Motor Type			PSC	PSC	PSC	PSC	PSC	PSC	PSC
Dimension	Unit (WxHxD)	Inch	23-3/5x25x23-3/5	23-3/5x25x23-3/5	23-3/5x25x23-3/5	29-1/7x25x29-1/7	29-1/7x32-7/8x29-1/7	29-1/7x32-7/8x29-1/7	29-1/7x32-7/8x29-1/7
	Packing(WxHxD)	Inch	24-4/5x26-1/5x24-4/5	24-4/5x26-1/5x24-4/5	24-4/5x26-1/5x24-4/5	30-3/10x26-1/5x30-3/10	30-3/10x34-4/5x30-3/10	30-3/10x34-4/5x30-3/10	30-3/10x34-4/5x30-3/10
Net / Gross Weight			Lbs	145/152	145/152	147/153	174/183	204/214	223/233
								233/243	